






















Construction & Environment

Result of long term cooperation between Trelleborg, end-users and OEMs, the Construction & Environment range has developed technical, specialized and innovative products.


Drain and sewer cleaning: specific products, high pressure resistance - **Industrial waste collection:** for fixed or mobile installations by suction, discharge - **Air protection:** hydraulic discharge of abrasive products - **Sandblasting and mortar:** for spraying of mortar and mixed concrete as well as dry products - **Concrete placement:** high pressure and abrasive resistance - **Bulk tank truck discharge**

Construction & Environment range


Applications	Product name		Diameter range (mm)	WP (bar)	Max. vacuum (bar)	Temp. (°C)
Drain and sewer cleaning						
	Flexible CANALKLER 250 S		13 - 38	250	-	-30 to +80 °C
	KLERIX		13 - 32	200	-	-30 to +80 °C
	ASPIKLER N		100 - 150	6	0.9	-30 to +80 °C
	ASSAINIX		90 - 150	4	0.8	-30 to +60 °C
Industrial waste collection						
	ZEPHIR S		30 - 150	-	0.8	-30 to +70 °C
	TRELLVAC		38 - 204	-	-	-40 to +90 °C
	ASPIVRAC S		50 - 200	1.5	0.8	-30 to +80 °C
Abrasive materials hydraulic and pneumatic handling						
	PERFORMER AR10		100 - 500	-	-	-30 to +70 °C
	PERFORMER		25 - 400	-	-	-30 to +100 °C
Sandblasting and mortar						
	TRELLBLAST S		13 - 32	10	-	-30 to +70 °C
	SABLEX		13 - 102	12	-	-30 to +70 °C
	SILEX		20 - 125	10	-	-30 to +70 °C
	PROJECTOR 40/100		25 - 75	10/20/40	-	-30 to +70 °C
Concrete pump and placement						
	PULSOR 170		50 - 150	85	0.8	-30 to +80 °C
	PULSOR 200		50 - 150	85	0.8	-30 to +80 °C
Bulk tank truck discharge						
	SUPERVRAC		75 - 152	7	-	-30 to +90 °C



END FLEX® flange/BLOC END® safety clamps



END FLEX® flange system is specially designed for PERFORMER AR, AD, CR or CD ranges.



BLOC END® coupling (with its special gasket), is specially designed for PERFORMER GL AD range.

Tube continuity: there is no contact between the product and the coupling's metal parts.